

## **Attestation of Conformity**

date: 15/04/2019

Gruppo Bardelli S.p.A. via G. Pascoli 4/6 - 20009 Vittuone (MI)

Plant address:	via Pordenone, 13 - Oderzo (TV)				
Year in which the CE marking was affixed:	2011				
Reference standard:	EN 14	411			
Product classification:	Glazed ceramic tiles dust pressed for internal/external wall/ceiling finishes				
Collection name:	Appiani				
Product reference:	Diva, Anthologhia, Metallica, Seta, Open Space, Mix, Denim, Libra, Regolo				
Product description:	all sizes				
Group:	BIb (0,5% < E < = 3%)				
CHARACTERISTICS					
Reaction to fire:	A1 and A1 fl				
Flexural tensile strength:					
breaking strength	>1700		N (for tiles with thickness < = 7,5 mm)		
breaking strength	>		N (for tiles with thickness > 7,5 mm)		
modulus of rupture	>45		N/mm2		
Resistance to thermal shocks:	passed				
Bond strength/adhesion:					
with cementitious adhesives	(cl.	) NPD	N/mm2		
with dispersion adhesives	(cl.	) NPD	N/mm2		
with reaction resines adhesives	(cl. ) NPD		N/mm2		
with mortar	available		N/mm2	ASTM C 482-02 (R-2009) sizes 1,2x1,2 cm/½"x½" - 2,5x2,5 cm/1"x1"	
Slipperiness:					
declared value	available		(test method DIN 51130)		
declared value	available			(test method DIN 51097)	
declared value	available		(test metho	(test method ANSI A 137.1) (DCOF)	
Skid resistance:					
declared value	NPD				
Durability - freeze/thaw cycle:	passe	d			
Release of dangerous substances:					
Release of Cadmium	NPD		mg/dm2		
Release of lead	NPD		mg/dm2		

NPD = no performance determined